

# SPECIFICHE TECNICHE



NovaSun HOME/PRO



NovaWind PRO



NovaEnergy PRO

## AX-5300



revisione 1.0 – 31/08/2009

<b>Sistema</b>	
CPU	Intel Atom Z510/Z530
CHIPSET	Intel US15W core logic
BIOS	Phoenix-Award
RAM	1GB DDR2 SO-DIMM
HDD	80GB SATA 2.5"
VGA	Intel Graphics Media Accelerator 500
WATCHDOG TIMER	255 livelli, 1-255 sec.
<b>Input/Output</b>	
COM	2 x RS-232
HDD	1 x SATA
PS/2	1 x Mini DIN PS/2 (mouse/tastiera)
USB	4 x USB 2.0
VGA	1 x 15pin D-sub
FLASH	1 x CF Card Reader Type II
LAN	1 x RJ-45 (10/100/1000Mbps)
AUDIO	1 x Line out, 1 x MIC in
<b>Caratteristiche</b>	
ALIMENTAZIONE	5V
TEMPERATURA	0 - 45 °C
UMIDITA'	10% - 90% (umidità relativa, senza condensa)
DIMENSIONI (A x L x P)	48 x 132 x 96 mm
PESO	600 g
MATERIALE BOX	Alluminio e acciaio
MONTAGGIO	Standard VESA, Din-rail opzionale
CERTIFICAZIONI	CE
<p>Ultima revisione aggiornata al 31 agosto 2009 e relativa alla versione 1.4.0 del dispositivo. Le caratteristiche potrebbero cambiare senza preavviso.</p>	