

SPECIFICHE TECNICHE



NovaSun LOG



NovaWind LOG



NovaEnergy LOG

EB-4300



revisione 1.1 – 31/08/2009



Sistema	
CPU	VIA Eden ULV 500MHz
BIOS	AMI BIOS
RAM	1GB DDR2
FLASH	Compact Flash Type II 2GB x266
VGA	VIA Unichrome PRO II, accelerazione MPEG4 e WMV9 (1920x1440)
LAN	Realtek 8100B
AUDIO	AC97 Codec VIA Vinyl VT1708
Input/Output	
COM	2 x RS-232
HDD	1 x 44pin Enhanced IDE
PS/2	1 x Mini DIN PS/2 (mouse/tastiera)
USB	3 x USB 2.0
VGA	1 x 15pin D-sub
FLASH	1 x CF Card Reader Type II
LAN	1 x RJ-45 (10/100Mbps)
AUDIO	1 x Line out, 1 x MIC in
Caratteristiche	
ALIMENTAZIONE	+5V @ 3.0A
TEMPERATURA	0 - 60 °C
UMIDITA'	0% - 90% (umidità relativa, senza condensa)
DIMENSIONI (A x L x P)	35 x 115 x 115 mm
PESO	505 g
MONTAGGIO	Standard VESA
CERTIFICAZIONI	CE, FCC

Ultima revisione aggiornata al 31 agosto 2009 e relativa alla versione 1.4.0 del dispositivo.
Le caratteristiche potrebbero cambiare senza preavviso.